



# **FINAL RESULT™**

## **FLOOR FINISH RESTORER**

**Extends the time between deep scrubbing/recoating and stripping/  
recoating, reducing labor costs and down-time of floors**

**Produces and maintains the highest gloss, wet-look**

**May be mopped on or applied with an auto scrubber**

### **DESCRIPTION**

Final Result is a maintenance product that enhances the surface and shine of most synthetic floor finishes. It cleans, repairs and restores a brilliant gloss to heavily trafficked floors. It extends the time between finish recoating by adding finish to the floor, replacing finish lost due to traffic.

### **WHERE TO USE**

Designed for vinyl composition tile, terrazzo and concrete floors. Best results are achieved with ultra-hi-speed burnishes of 1,000 RPM or more. Recommended for use starting a few days after application of floor finish and then 2 to 4 times per week for gloss maintenance.

### **DIRECTIONS**

#### **HAND MOPPING APPLICATION**

##### **SUPPLIES NEEDED**

Finish Mop  
Bucket & Wringer or Auto Scrubber  
Burnisher  
Genie or M/A Blue Blend Pads

The floor must be thoroughly clean before using Final Result. If this product is applied to a dirty floor the burnishing step will fuse the dirt into the finish.

Clean the floor by mopping with a solution of Ultra-Gloss Neutral Cleaner, Da-Clean Neutral Cleaner, M.P.C. or D-C Plus and cold water. Or clean with an auto scrubber.

After the floor has been thoroughly cleaned, prepare a clean mop bucket to with 1 gallon of Final Result to 4 to 8 gallons of cold water (1:4 to 1:8). The amount of Final Result added is relative to how dirty the floor is and how much finish has been lost due to traffic. Less is normally better. The best dilution can be determined after the first few times the product is used.

Using a clean finish mop, dip the mop and

wring. Apply a thin to moderate coat of Final Result to all buffable areas of the floor. Do not apply to edges of the floor. Avoid puddles.

Allow Final Result to dry completely before burnishing. Drying time should be about 15 minutes. The floor must be dry before burnishing. If longer drying time is required the solution was laid too heavily.

Burnish the floor to a high gloss using a propane buffer or an ultra-hi-speed electric burnisher. Use a Damon Genie Pad or an M/A Blue Blend pad. Change or flip the pad to a clean side every 500 to 1,000 square feet. Changing and flipping the pads will prevent dusting. After burnishing, dust mop the floor with an un-treated dust mop.

Clean & store pads and equipment properly.

#### **ONE-STEP CLEAN & APPLY AUTO SCRUBBER APPLICATION**

##### **SUPPLIES NEEDED**

Auto Scrubber  
Scrubbing Pads (green, blue, etc.)  
Finish Mop  
Bucket & Wringer  
Burnisher  
Genie or M/A Blue Blend Pads

Add 2 to 4 ounces of Final Result for each gallon of cold water in the solution tank. The amount of Final Result added is relative to how dirty the floor is and how much finish has been lost due to traffic. Less is normally better. The best dilution can be determined after the first few times the product is used.

Scrub in a single pass releasing enough solution to loosen dirt. In areas that are heavily soiled do a doubled pass releasing the solution with the squeegee up on the first pass and picking it up on the second pass.

Follow the scrubber with a wet mop, damp with cold water, picking up any puddles or streaks.

Puddled solution that is allowed to dry may not burnish to the desired high gloss. Allow Final Result to dry completely before burnishing. Drying time should be no more than about 15 minutes.

Burnish the floor to a high gloss using a propane buffer or an ultra-hi-speed electric burnisher. Use a Damon Genie Pad or an M/A Blue Blend pad. Change or flip the pad to a clean side every 500 to 1,000 square feet. Changing and flipping the pads will prevent dusting. After burnishing, dust mop the floor with an un-treated dust mop.

Clean and store pads and equipment properly.

## PACKAGING

Case of 4 one gallon jugs. Packaging material is recyclable.

## SPECIFICATIONS

Average static coefficient of friction by A.S.T.M D-2047-75 James Machine is 0.70.

Volatile Organic Compounds (V.O.C.) 14 g/l - 1.4%

A greenish-white liquid with a mild cherry fragrance.

**CAUTION:** Floors are slippery when wet. To prevent falls, exercise care when working, wear proper footwear and block off traffic with "Wet Floor" signs until the floor is completely dry. Use only as directed. If in question as to adhesion, a test patch is recommended. Do not mix with any other product because poor performance could result. Do not pour unused product back into the original container.



Damon manufactures a complete line of products for your floor care program. For more information, contact us at 1-800-362-9850 or [info@DamonQ.com](mailto:info@DamonQ.com) or visit [DamonQ.com](http://DamonQ.com).