Section 1 - Identification

Product Name: Ultimet® 21 Plus A polymer floor finish. Revised: 4/28/15

Damon Industries, Inc. 12435 Rockhill Ave NE Alliance, Ohio 44601 U.S.A. 1-800-362-9850 1-330-821-5310 1-330-821-6355 Fax info@DamonQ.com

24 HOUR EMERGENCY RESPONSE

Trade secret*

128-37-0

1-800-535-5053 (U.S. & Canada) 001-352-323-3500 (International)

Number: DMN0202

1%

<1 ppm

Section 2 - Hazards Identification

This product does not meet any of the conditions requiring GHS label warning, pictogram or prevention statements. See Sections 4 and 6 below for standard non-GHS safety and emergency information.

Section 3 - Composition / Information on Ingredients Ingredient C.A.S. No. Concentration Water 7732-18-5 77% 12% Acrylic polymer(s) Trade secret* Dipropylene glycol methyl ether 34590-94-8 3% 2% Ethanol, 2-(2-ethoxyethoxy)-111-90-0 Tris(2-butoxyethyl) phosphate 78-51-3 2% Isodecyl benzoate 131298-44-7 1% Zinc compound(s) Trade secret* 1% 2-Propenoic acid, polymer with ethene, potassium salt 27515-34-0 1%

Section 4 - First Aid Measures

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, lifting upper and lower eyelids occasionally. If eye irritation persists: Get medical attention. **Skin Contact:** Wash exposed area with soap and water. If irritation develops and persists, get medical attention. **Inhalation:** Move exposed person to fresh air. If irritation persists, get medical attention.

Ingestion: If the product is swallowed, do NOT induce vomiting. If affected person is conscious, give a glass of water or milk to drink. Get medical attention.

Section 5 - Fire-Fighting Measures

Extinguishing Media: Any Unusual Fire And Explosion Hazards: None.

Ammonium salt of mofified styrene acrylic polymers

Butylated hydroxytoluene (BHT)

Special Fire Fighting Procedures: None.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Wipe or mop up small spills. Larger spills can be collected into clean pails or drums for later use or washed to a sanitary sewer with plenty of water.

Section 7 - Handling and Storage

Store at temperatures between 40° and 100° F.

Empty containers retain product residue and may be hazardous. Observe all precautions given in this data sheet.

Section 8 - Exposure Controls / Personal Protection							
Ingredient	C.A.S. No.	Concentration	TWA(source)	STEL	Ceiling		
Dipropylene glycol methyl ether	34590-94-8	3%	100 ppm(1,2)	150 ppm(2)	-		
Butylated hydroxytoluene (BHT)	128-37-0	<1 ppm	10mg/m ³ (2)	-	-		

(1)=OSHA (2)=NIOSH (3)=ACGIH (4)=CANADA TWA=8 hr Time Weighted Average STEL=15 minute TWA Ceiling=Instantaneous Ingredients not shown either have no known limits or are below reportable levels in section 3 above.

Ventilation: Normal room ventilation.

Respiratory Protection: None when used as directed.

Gloves: Persons with sensitive skin may wish to use rubber or latex gloves when skin contact is possible.

Eye Protection: If eye contact with concentrate is possible, wearing safety glasses with side shields, especially for contact lens wearers, is a good idea.

Other Protective Equipment: None.

^{*} This is not a trade secret of Damon Industries, it is a trade secret of the manufacturer of the ingredient. The remaining ingredients are not reportable as described in Appendix D to Sec. 1910.1200 Table D.1.

Section 9 - Physical and Chemical Properties					
Appearance and Odor: A white liquid with acrylic odor.					
Odor Threshold: Not Available	Vapor Pressure: Not Available				
pH: concentrate 8.5 ± 0.5	Vapor Density: Not Available				
Melting Point: Not Available	Relative Density (Specific Gravity): 1.04				
Freezing Point: Not Available	Solubility(ies): Water: 100%				
Boiling Point, Initial: 212° F.	Partition coefficient: Not Available				
Boiling Range: Not Available	Auto-ignition Temperature: Not Available				
Flash Point: None	Decomposition Temperature: Not Available				
Evaporation Rate: ~1 (Water = 1)	Viscosity: Same as water.				
Flammability: (solid, gas): Not Applicable	Volatiles Percent: 80%				
Upper Explosive Limit: Not Available	V.O.C.: 4.3% - 44 grams/liter				
Lower Explosive Limit: Not Available					

Section 10 - Stability and Reactivity

Incompatibility: None Hazardous Decomposition Products: None

Section 11 - Toxicological Information

Primary Routes of Entry: X Skin contact; Skin absorption; Inhalation; X Ingestion

Potential Health Effects:

Eyes - may cause irritation, redness, tearing.

Skin - may cause irritation.

Swallowing - may cause irritation to the mouth and throat.

Breathing - Possibly irritating if over exposed.

Section 12 - Ecological Information

Not hazardous, but do not dispose of in the environment.

Section 13 - Disposal Considerations

Waste Disposal Method: Wash to a sanitary sewer with a large amount of water.

Section 14 - Transport Information

D.O.T. Hazard Class: Not considered hazardous by D.O.T., I.M.C.O., I.A.T.A. or U.N.

Section 15 - Regulatory Information

The components of this product are on the TSCA inventory of chemical substances.

Section 313 Supplier Notification: This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and CFR 372.

Chemical Name	C.A.S. No.	% By Weight	Lbs./Gallon
Dipropylene glycol methyl ether	34590-94-8	3.3	0.37
2-(2-ethoxyethoxy)-ethanol	111-90-0	2.4	0.27

Section 16 - Other Information

NFPA: H:1 F:0 I:0 **HMIS**[®] **III:** H:1 F:0 P:0 These ratings estimates are to be used only with a fully implemented training program in the workplace. NFPA[®] is a mark registered by the NFPA. HMIS[®] is a mark registered by the NPCA.

Replaces sheet dated 7/20/06. GHS conversion.

The information accumulated herein is believed to be accurate but is not warranted to be. Recipients are advised to confirm in advance that the information is current, applicable, and suitable to their circumstances.