

Section 1 - IdentificationProduct Name: **Slam Dunk**TM Water-based wood floor finish.

Revised: 4/28/15

Damon Industries, Inc. 12435 Rockhill NE Alliance, Ohio 44601 U.S.A.	1-800-362-9850 1-330-821-5310 1-330-821-6355 Fax info@DamonQ.com	24 HOUR EMERGENCY RESPONSE 1-800-535-5053 (U.S. & Canada) 001-352-323-3500 (International)
---	---	---

Section 2 - Hazards Identification

This product does not meet any of the conditions requiring GHS label warning, pictogram or prevention statements. See Sections 4 and 6 below for standard non-GHS safety and emergency information.

Section 3 - Composition / Information on Ingredients

Ingredient	C.A.S. No.	Concentration
2-(2-butoxyethoxy)ethanol	112-34-5	5%
N-methyl-2-pyrrolidone	872-50-4	5%
2-Butoxyethanol	111-76-2	5%

The remaining ingredients are not reportable as described in Appendix D to Sec. 1910.1200 Table D.1.

Section 4 - First Aid Measures

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, lifting upper and lower eyelids occasionally. If eye irritation persists: Get medical attention.

Skin Contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Inhalation: Move the affected person to fresh air. If irritation persists get medical attention.

Ingestion: Wash out mouth with water. Move victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Section 5 - Fire-Fighting Measures

Extinguishing Media: Suitable for the surrounding fire.

Special Fire Fighting Procedures: None.

Unusual Fire And Explosion Hazards: None.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Dilute small spills with water and mop up. Alternatively, absorb with an inert dry material and place in an appropriate waste disposal container. Prevent entry into sewers, water courses, basements or confined areas.

Section 7 - Handling and Storage

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Section 8 - Exposure Controls / Personal Protection

Ingredient	C.A.S. No.	Concentration	TWA(source)	STEL	Ceiling
2-Butoxyethanol	111-76-2		50 ppm(1), 5 ppm (2), 20 ppm (3), 25 ppm (4)	75 ppm(4)	-

(1)=OSHA (2)=NIOSH (3)=ACGIH (4)=CANADA TWA=8 hour Time Weighted Average STEL=15 minute TWA Ceiling=Instantaneous
Ingredients not shown either have no known limits or are below reportable levels in section 3 above.

Ventilation: Good room ventilation.

Respiratory Protection: None, unless exposure limits will be exceeded.

Gloves: Use rubber or latex gloves. Disposable latex gloves may be used.

Eye Protection: If splashing of the product is likely, the use of safety glasses with side shields, especially for contact lens wearers, is suggested.

Other Protective Equipment: None.

Section 9 - Physical and Chemical Properties

Appearance and Odor: A light yellow liquid with a bland odor..	
Odor Threshold: Not Available	Vapor Pressure: < 30 mm Hg
pH: concentrate 8.0 ± 0.5	Vapor Density: < 1 (Air = 1)
Melting Point: Not Available	Relative Density (Specific Gravity): 1.04
Freezing Point: Not Available	Solubility(ies): Water: 100%
Boiling Point, Initial: 212° F.	Partition coefficient: Not Available
Boiling Range: Not Available	Auto-ignition Temperature: Not Available
Flash Point: >200°F. (ASTM D-56 closed cup)	Decomposition Temperature: Not Available
Evaporation Rate: ~1 (Water = 1)	Viscosity: Same as water.-
Flammability: (solid, gas): Not Applicable	Volatiles Percent: 99%
Upper Explosive Limit: None	V.O.C.: 254 grams/liter
Lower Explosive Limit: None	

Section 10 - Stability and Reactivity

Incompatibility: None

Hazardous Decomposition Products: None

Section 11 - Toxicological Information

Primary Routes of Entry: Skin contact; Skin absorption; Inhalation; Ingestion

Potential Health Effects:

Eyes - No known significant effects or critical hazards.

Skin - No known significant effects or critical hazards.

Swallowing - No known significant effects or critical hazards.

Breathing - Excessive inhalation in poorly ventilated areas may cause respiratory irritation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.

The LD₅₀ of 2-Butoxyethanol is 450mg/kg and the LC₅₀ is 700ppm 7hr

The LD₅₀ of n-Methyl-2-pyrrolidone is 4,200mg/kg

The LD₅₀ of Diethylene glycol monobutyl ether is 7,292mg/kg N.D.

LD₅₀: of mixture not established. The LD₅₀ of 2-(2-butoxyethoxy)ethanol is 2,700 mg/kg (rat), N-methyl-2-pyrrolidone is 3,914 mg/kg (rat), 2-butoxyethanol is 450 mg/kg (rat)

Section 12 - Ecological Information

Do not dispose of unusable product in the environment. Do not allow run-off into public waterways.

Section 13 - Disposal Considerations

Waste Disposal Method: Disposed of only as permitted by federal, state and local regulatory authorities.

Section 14 - Transport Information

D.O.T. Hazard Class: Not considered hazardous by D.O.T., I.M.C.O., I.A.T.A. or U.N.

Section 15 - Regulatory Information

The components of this product are on the TSCA inventory of chemical substances.

Section 313 Supplier Notification: This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and CFR 372.

Chemical Name	C.A.S. No.	% By Weight
2-(2-butoxyethoxy)ethanol	112-34-5	4%
n-Methyl-2-pyrrolidone	872-50-4	3.2%
2-Butoxyethanol	111-76-2	1.3%

Section 16 - Other Information

NFPA: H:1 F:0 I:0 **HMIS® III:** H:1 F:0 P:0 Maximum Personal Protection: B

These ratings estimates are to be used only with a fully implemented training program in the workplace. NFPA® is a mark registered by the NFPA. HMIS® is a mark registered by the NPCA.

Replaces sheet dated 4/19/06. GHS conversion.

The information accumulated herein is believed to be accurate but is not warranted to be. Recipients are advised to confirm in advance that the information is current, applicable, and suitable to their circumstances.