

# +Material Safety Data Sheet

Number: **DMN0459**

## Product Name: **Perfection**

A polymer floor finish.

Revised: 4/9/08

Damon Industries, Inc.  
Box 2120  
Alliance, OH 44601

24 hour Emergency Only phone: 1-800-535-5053  
Information phone: 1-800-362-9850 or 330-821-5310  
fax: 330-821-6355

### Section 2 - Composition / Information on Hazardous Ingredients

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Percent</u>	<u>Carcinogen</u>
2-Methoxymethylethoxy propanol	34590-94-8	2 - 10%	No
2-(2-ethoxyethoxy)-ethanol	111-90-0	2 - 10%	No

### Section 3 - Hazards Identification

**Emergency Overview:** Liquid is irritating to the eyes and may be irritating to the skin. A white liquid with acrylic odor. Product is water based and presents little hazard in a fire.

**Health Hazards:** Irritant

**Physical Hazards:** None

**Primary Routes of Entry:**  Through Skin  Inhalation  Ingestion

#### Potential Health Effects:

**Eyes** - may cause irritation, redness, tearing.

**Skin** - may cause irritation.

**Swallowing** - may cause irritation to the mouth and throat.

**Breathing** - Possibly irritating if over exposed.

### Section 4 - First Aid Measures

**Eye Contact:** Immediately flush eyes with water for at least 15 minutes, lifting upper and lower eyelids occasionally. If irritation persists, get medical attention.

**Skin Contact:** Wash exposed area with soap and water. If irritation develops and persists, get medical attention.

**Inhalation:** Move exposed person to fresh air. If irritation persists, get medical attention.

**Ingestion:** If the product is swallowed, do NOT induce vomiting. If affected person is conscious, give a glass of water or milk to drink. Get medical attention.

### Section 5 - Fire-Fighting Measures

**Flash Point:** none. (ASTM D-56 closed cup)

**Lower Explosive Limit:** Not Applicable

**Upper Explosive Limit:** Not Applicable

**Extinguishing Media:** Any

**Special Fire Fighting Procedures:** None.

**Unusual Fire And Explosion Hazards:** None.

### Section 6 - Accidental Release Measures

**Steps To Be Taken If Material Is Released Or Spilled:** Wipe or mop up small spills. Larger spills can be collected into clean pails or drums for later use or washed to a sanitary sewer with plenty of water.

### Section 7 - Handling and Storage

Store at temperatures between 40° and 100° F.

Empty containers retain product residue and may be hazardous. Observe all precautions given in this data sheet.

### Section 8 - Exposure Controls / Personal Protection

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Percent</u>	<u>TWA(source)</u>	<u>STEL</u>	<u>Ceiling</u>
2-Methoxymethylethoxy propanol	34590-94-8	4.6%	100 ppm(1,2,3,4)	150 ppm(2,3,4)	-
2-(2-ethoxyethoxy)-ethanol	111-90-0	3%	No limits have been established.		
<small>(1)=OSHA (2)=NIOSH (3)=ACGIH (4)=CANADA TWA=8 hr Time Weighted Average STEL=15 minute TWA Ceiling=Instantaneous</small>					

**Ventilation:** Normal room ventilation.

**Respiratory Protection:** None when used as directed.

**Gloves:** Persons with sensitive skin may wish to use rubber or latex gloves when skin contact is possible.

**Eye Protection:** If eye contact with concentrate is possible, wearing safety glasses with side shields, especially for contact lens wearers, is a good idea.

