



AMF-77™

General Purpose Cleaner-Degreaser

DI-PHASE CLEANER - Versatile, fast-acting on grease and soil

NON-FLAMMABLE - Safe for user and environment

UNIQUE SOLVENT SYSTEM - Non-butyl, no health hazards

CONCENTRATED - Economical to use

Damon AMF-77 is a heavy-duty, synthetic cleaner/degreaser concentrate that works like a detergent on dirt and like a solvent on grease and oil. Its unique formulation leaves no residue, is non-flammable, dilutes with water, and contains no dangerous solvents.

At high use dilutions, AMF-77 is the perfect cleaner for stainless steel, Formica, painted surfaces, and food service equipment. At lower dilutions, the cleaner is ideal for grills, filters, engines, and for small parts stripping. At recommended dilutions it is also an excellent car and truck body washer that will not harm paint, but removes road oil and grime. AMF-77 is excellent for cleaning aluminum, and will remove moderate oxidation. AMF-77 can cut through grease and grime on any hard surface at dilutions up to 90 to 1. This highly concentrated formulation is economical to use because of its low in-use dilution cost.

DI-PHASE CLEANER

This unique blend of detergents and solvents promotes higher dissolving power against stubborn accumulations on auto and truck engines, chassis and exteriors, cement floors and many other surfaces.

NON-FLAMMABLE

AMF-77's non-flammable formulation means it is safer for both the user and the environment.

UNIQUE BUFFERING SYSTEM

At a normal dilution, AMF-77 retains full non-caustic cleaning power for extended

usefulness. The competing product solution is initially caustic, which can be harmful to the user and to some surfaces. Furthermore, its cleaning power declines quickly, working with less efficiency than AMF-77.

DIRECTIONS:

MACHINE SCRUBBING OF FLOORS: Dilute AMF-77 at 2 - 4 ounces per gallon of water for light to moderate cleaning.

HAND SCRUBBING FLOORS WITH SCRUB BRUSH: Dilute AMF-77 at 2 ounces per gallon of water for general cleaning.

CEMENT AREAS SUCH AS SIDEWALKS, DRIVE THRU, AND DUMPSTER AREA: Dilute AMF-77 at 8 ounces per gallon of water.

CLEANING ENTRANCE MATS: Dilute AMF-77 at 8 ounces per gallon of water.

For cleaning the following surfaces dilute AMF-77 at 12 ounces per gallon of water.

For additional instructions see the product label and specific procedure sheets.

PACKAGING: 55 gallon plastic drums. Packaging material is recyclable.

AMF-77.pub - 07/09/02