



Brite-Buff™

SPRAY-BUFFING COMPOUND

Restores shine on most hard floor finishes
May be sprayed or mopped on
Use with low speed 175 to 300 RPM buffers

DESCRIPTION

BRITE-BUFF is a water based spray buffing compound for hard finishes such as Ultimet HP and Ultimet 21 *Plus*. Cleans and polishes as you buff with a red or white pad and a 175 to 300 rpm buffer. Also works well with 1,000 rpm and up burnishers. Finish looks better and lasts longer. Pleasant fragrance.

WHERE TO USE

May be used on vinyl, vinyl asbestos, vinyl composition, asphalt tile and terrazzo.

DIRECTIONS

DO NOT DILUTE THIS PRODUCT.

Very little Brite-Buff is needed to build a high gloss. Typically a red or white buffing pad is used, but the best floor pad to use depends on the type of floor, type of finish and the speed and weight of the machine. Your Damon representative will help you select the correct pad.

SPRAY METHOD

Using a trigger sprayer, spray a fine mist on an area of the floor that can be buffed within a few minutes. Buff with a rotary floor machine until the floor is dry and polished.

MOP-ON METHOD

Coverage: 3,000 square feet per gallon. Pour Brite-Buff into a clean mop bucket. Dip a clean finish mop into the solution and wring until damp. Damp mop an

area that can be buffed within a few minutes. Buff with a rotary floor machine until the floor is dry and polished.

PACKAGING

Case of 4 one gallon jugs. Packaging material is recyclable.

SPECIFICATIONS

Average static coefficient of friction by A.S.T.M D-2047-75 James Machine is 0.55 or greater.

Volatile Organic Compounds (V.O.C.)
13 g/l - 1.3 %

Light blue liquid with mild floral odor.



Brite-Buff.pub - 7/24/12