



# ***CORE-SURE™***

## **COME BACK INSURANCE**

- **Reduce come backs**
- **Fix tiny leaks that cannot be easily located**
- **Provide an added benefit for your customers**

**COME BACK INSURANCE** — After repairing the radiator, put one tablespoonful of CORE-SURE™ in either the top or bottom of the radiator and disperse it throughout with compressed air. Not even you will be able to tell it is there. When the radiator is placed in service, any leaks or seepage that might develop later will be completely sealed.

CORE-SURE™ combines linseed meal and a thermosetting resin for superior results. The meal swells up to seal the leaks and the resin makes the repair longer lasting. If a radiator is in very bad shape more new leaks may develop than CORE-SURE™ can handle. Adding more CORE-SURE™ will work up to a point. Too much could cause other problems and more than two tablespoons in an automotive is never recommended.

**CORROSION PREVENTION** — CORE-SURE™ also contains an effective corrosion inhibitor for copper and brass. This inhibitor gives added protection on top of that provided by coolant. It is not meant to take the place of anti-freeze or coolant.

**WATER PUMP LUBRICATION** — Another plus for both your customer and you. It lubricates without oil.

**NON-SELECTIVE** — CORE-SURE™ works equally well in water and anti-freeze, yet it is not activated by the small amount of water left in the core from testing.

**REDUCE COSTS** — Make more money by eliminating those costly come-backs by using CORE-SURE™ as insurance. You also are benefiting the customer by protecting his cooling system from corrosion.

CORE-SURE™ may also be used to seal leaks in a radiator or heater while on the car or truck. — Run the motor until the coolant reaches normal operating temperature. Then put one or two tablespoonsful of CORE-SURE™ into the radiator. Run engine until leaks are stopped.

**NOTE:** For larger radiators a proportionately larger amount of CORE-SURE™ will be required.

CoreSure.pub - 3/14/04