




This product meets the Green Seal™ Standard for Floor-Care Products for Industrial and Institutional Use, GS-40, based on its reduced human and aquatic toxicity and reduced smog production potential.

## G2 Green Finish

### High Performance Floor Coating



### Features

- Contains no butyl, harsh alkalis, zinc, phthalates or APEO surfactants
- Ultra-low 1.0% VOC content meets California's new 2011 standard
- Low odor - ammonia-free
- Multi-surface, all-purpose formula for all maintenance systems
- Easy-to-apply, levels nicely and dries to a high gloss
- Combination seal and finish
- Large area coverage – up to 3,000 sq. ft. per gallon
- Fast-drying – 20 minutes under normal conditions
- Slip-resistant – UL classified

### Properties\*

Type .....	Acrylic Emulsion
Form .....	Opaque Liquid
Odor .....	Bland
Color .....	Milky White
Film Clarity .....	Clear
Weight Per Gallon.....	8.61 Lbs.
pH .....	7.1
Floor Solids .....	20%
Storage Stability .....	Min. 1 Year
Freeze/Thaw.....	Do Not Freeze
V.O.C.....	1.0%

\* Properties are typical and subject to usual manufacturing tolerances

## 8201 FF

© 2011 Essential Industries, Inc. J1811  
LT-9000S8201FF

Merton, Wisconsin 53056-0012  
Phone: (262) 538-1122  
www.essind.com

 **ESSENTIAL®**  
**INDUSTRIES**

Reorder From  
DAMON INDUSTRIES, INC.  
Box 2120  
Alliance OH 44601  
1-800-362-9850  
info@DamonQ.com


# Green Essence™



This product meets the Green Seal™ Standard for Floor-Care Products for Industrial and Institutional Use, GS-40, based on its reduced human and aquatic toxicity and reduced smog production potential.

## G2 Green Finish

### High Performance Floor Coating



# TRAINING

## Directions

**APPLICATION:** 1. Strip floors to remove old waxes, sealers and finishes. 2. Rinse thoroughly and let dry. 3. With clean equipment apply thin, even coats of G2 Green Finish. 4. Under normal conditions, allow to dry for 20 minutes between coats. 5. For best results, apply a maximum of 4 coats in 24 hours. 6. Allow 48 hours for the finish to reach full cure before wet cleaning. Burnishing will speed cure time.

**NOTE:** For stripping and maintaining asbestos containing tile, follow OSHA or EPA guidelines.

**NOTE:** DO NOT FREEZE

**COVERAGE:** One gallon covers up to 3,000 square feet.

**MAINTENANCE: Daily:** 1. Sweep or dust mop frequently to remove gritty soil. 2. Use our Green Clean to damp mop spills as they occur. Damp mop or auto-scrub nightly with Green Clean. 3. Buff if desired with high speed equipment and blended hair pads. **Weekly:** 1. To repair and deep clean floor, apply our Green Restore with mop or auto-scrubber. 2. Allow floor to dry. 3. Burnish floor with high speed equipment. This finish also responds to spray buffing with conventional speed equipment. Note: Always dust mop after burnishing or spray buffing. **Periodic Recoating:** 1. Dust mop entire floor then scrub aggressively using our Green Restore and auto-scrubber with a red or green pad. 2. Rinse floor and allow to dry. 3. Apply G2 Green Finish. **Stripping G2 Green Finish:** Strip with Green Strip diluted 1:4.

Contains no butyl, harsh alkalies, zinc, phthalates or APEO surfactants. Ultra-low 1.0% VOC content meets California's 2011 standard.

### DISPOSAL

**PRODUCT:** Dispose of excess product in accordance with local, state, and federal regulations.

**CONTAINER:** Please recycle HDPE container.

### VENTILATION

No special ventilation needed. However, use of adequate ventilation is good industrial practice.

### IMPROPER USE OR APPLICATION

**IMPROPER USE:** May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

**IMPROPER APPLICATION:** Over application of finish may cause floor to be tacky, streaked and/or ghosted looking, dull and prone to black marking and scuffing.

### FIRST AID

**EYES & SKIN:** Flush with water (eyes 15 minutes). If irritation persists, seek medical attention.

**INGESTION:** If swallowed, give 2-3 large glasses of water. Seek medical attention.

# 8201 FF

© 2011 Essential Industries, Inc. J1811



Merton, Wisconsin 53056-0012  
Phone: (262) 538-1122  
www.essind.com

 **ESSENTIAL®**  
**INDUSTRIES**