



Daco[®] Super-Strip

High butyl for the most demanding stripping jobs

Fast acting

A super-concentrated floor stripping agent economical and effective for low to very heavy floor stripping.

DESCRIPTION

Highest butyl and high caustic stripper. Easy to rinse and fast acting. Most aggressive stripping action. Moderate odor.

Daco Super-Strip has been one of Damon's best selling products for many years. Its present state-of-the-art formula has evolved over the past twenty years to take advantage of the best science has to offer.

Daco Super-Strip is designed to remove all types of water emulsifiable finishes, waxes and sealers from resilient floors, including terrazzo, vinyl, vinyl asbestos, asphalt tile, and many others. It does this without obnoxious or flammable fumes.

HIGHLY CONCENTRATED

Daco Super-Strip is very economical to use as a result of its high concentration. For most stripping jobs it dilutes at 1:15 or 1:20. One gallon will strip approximately 750-1,000 square feet.

FAST ACTING

Daco Super-Strip's special blend of caustic and solvents penetrates quickly to soften wax. You can strip more square feet in the same amount of time because you spend less time waiting. Daco Super-Strip will soften two or three coats of finish in five minutes. Four or more coats will take ten to fifteen minutes depending on the amount of burnishing that has been done.

LESS HAZARDOUS

This makes the product safer for workers and means that people in other parts of the building will not be bothered by its use. The product is not as slippery and does not burn skin as quickly as many other strippers.

SAFE FOR ALL FLOORS

Daco Super-Strip is very safe for asphalt tile flooring. It does not bleach nor soften it as can happen with some products. It is user-friendly because slight over-use does not spell trouble.

Heavy 1:2

Medium 1:3

pH 12.5

Caustic 2%



Rubber gloves, safety glasses, non-slip impervious shoes or boots, well ventilated room

PACKAGING: One gallon plastic jugs packed four per case and five gallon plastic containers. All packaging material is recyclable.

SPECIFICATIONS

Non-Volatile Solids:	15%
Volatile Organic Compounds (VOC).....	31 g/l - 3.0%
Appearance:	White
Odor:.....	Mild
Type:.....	Acrylic co-polymer
Leveling:	Good
Recoating and Patching:	Superior
Foaming in Bucket:.....	None
Mop Drag:.....	None
Film Dry Time:	30 minutes
Walk On Time:.....	30 minutes
Time Before Recoat:.....	30-60 minutes
Time Before Buffing:.....	1 Hour
Film Gloss:.....	High
Film Color Stability:.....	Excellent
Slip Resistance: ASTM D-2407-75 James Machine coefficient	0.5 or higher
Scrubbability:	Excellent
Film Type:.....	restorable
Resistance to Water:	Excellent
Resistance to Scuffing and Heel Marks:.....	Excellent
Durability:.....	Exceptional
Coverage per gallon:	1,200 to 2,000 Sq. Ft.
Buffing Speed:	1,000 - 3,000 RPM

CAUTION: Floors are slippery when wet. To prevent falls, exercise care when working, wear proper footwear and block off traffic with "Wet Floor" signs until the floor is completely dry. Use only as directed. If in question as to adhesion, a test patch is recommended. Do not mix with any other product because poor performance could result. Do not pour unused product back into the original container.



Damon manufactures a complete line of products for your floor care program. For more information, contact us at 1-800-362-9850 or info@DamonQ.com or visit DamonQ.com.