



Ultimet® Nano Floor Finish

- Nano-zinc cross-linking provides superior:
 - Lay-down gloss - Durability - Soil resistance
 - Gloss build - Mark resistance - Dry and recoat times
- Ammonia-free for dramatically-reduced odor.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low-emissions formula - less than 1% V.O.Cs.
- Ultra fast drying - 20 minutes under normal conditions.

DESCRIPTION

ULTIMET Nano is a revolutionary floor finish that combines deep gloss, high durability and ease-of-use into one product. High molecular weight acrylic polymers and our patented nano-zinc cross-linking system produce a beautiful, long lasting shine that resists black marking, scuffing and soil penetration. Ultimet Nano is perfect for use in hospitals and nursing homes because of its very little odor and the ultra fast drying time. Ultimet Nano is also ideal for limited maintenance settings such as classrooms, patient rooms, and offices because of its durability. It does respond well to occasional burnishing, making it suitable for retail establishments, hallways and other maintained areas.

WHERE TO USE

May be used on vinyl, vinyl asbestos, vinyl composition, and asphalt tile.

DIRECTIONS

PREPARATION

Floors must be clean, dry, and free of old finish or wax before the application of Ultimet Nano. Strip the floor thoroughly using any of Damon's quality floor strippers following label directions. Rinse until no residue remains.

APPLICATION

Use a clean, broken-in mop or a finish mop and a clean bucket. Line the bucket with a

trash liner to prevent contamination of finish and make clean up easier. For best results, apply a maximum of 4 coats in 24 hours. Better results are obtained if four or five thin coats are applied instead of two or three heavier coats. Allow to dry 20 minutes between coats.

HOW TO MAINTAIN

Dust mop daily to prevent grit from dulling the shine. Depending on the degree of soil, either damp mop, wet mop, or scrub with a floor machine using Ultimet® Neutral Cleaner, Da-Clean™ A.P.C., Da-Clean™ Neutral Cleaner or D-C® Plus.

RESTORING

Use Damon's Final Results™ restorer with an ultra high speed (1,000 - 3,000 RPM) burnisher.

REMOVAL

Ultimet Nano can be removed using any of Damon's quality floor strippers.

PACKAGING

One gallon plastic jugs packed four per case. Packaging materials are recyclable.



SPECIFICATIONS

Non-Volatile Solids:.....	20%
Volatile Organic Compounds (VOC)	0.59%
Appearance:.....	White
Odor:.....	Mild
Type:.....	Nano-zinc cross-linked acrylic
Leveling:.....	Superior
Recoating:.....	Superior
Foaming in Bucket:	None
Mop Drag:	None
Walk On Time:	20 minutes
Time Before Recoat:	20 minutes
Time Before Buffing:	60 minutes
Film Gloss:	High
Film Color Stability:	Excellent
Slip Resistance: ASTM D-2407-75 James Machine coefficient	0.60 or higher
Scrubability:	Excellent
Film Type:	Restorable
Resistance to Water:.....	Excellent
Resistance to Scuffing and Heel Marks:	Excellent
Durability:.....	Exceptional
Coverage per gallon:.....	2,000 to 3,000 Sq. Ft.
Buffing Speed:	1,000 - 3,000 RPM

CAUTION: Floors are slippery when wet. To prevent falls, exercise care when working, wear proper footwear and block off traffic with “Wet Floor” signs until the floor is completely dry. Use only as directed. If in question as to adhesion, a test patch is recommended. Do not mix with any other product because poor performance could result. Do not pour unused product back into the original container.



Damon manufactures a complete line of products for your floor care program. For more information, contact us at 1-800-362-9850 or info@DamonQ.com or visit DamonQ.com.